Project Information Form

Project Title	Impact and Feasibility Study of Solutions for Doubling Heavy Vehicles
University	The University of Alabama at Birmingham
Principal Investigator	Nasim Uddin
PI Contact Information	Professor Department of Civil, Construction, and Environmental Engineering The University of Alabama at Birmingham 1075 13 th Street South Birmingham, Alabama 35294-4440 Telephone: (205) 934-8432, Fax: (205) 934-9855 Email: nuddin@uab.edu
Funding Source(s) and Amounts Provided (by each agency or organization)	UTC: UAB (\$99,261), UCF (\$51,000), and FIU (\$49,993) Match: ALDOT (\$99,261), FDOT (\$51,000), FIU (\$19,294)
Total Project Cost	\$443,648
Agency ID or Contract Number	DTRT12GUTC12 RC614-G1
Start and End Dates	May 1st, 2012 – October 31th, 2013
Brief Description of Research Project	The objective of this research is to quantify the effect of meeting increasing freight demands with heavier trucks to reduce the growth in the number of trucks on the road; and to compare the effect of heavier trucks to the effect of doubling the number of heavy vehicles under the present legal weight restrictions. Ongoing research tasks includes the following: (1) Development of computer models of vehicle, bridge, and surface roughness (2) Dynamic Analysis of bridge due to moving vehicles
	(3) Fatigue Life Assessment; and estimating the bridge network costs associated with changes in the limits on legal and permit gross weight, axle weights, or axle configurations
	(4) Quantification of better or worse bridge durability and longevity when compared to increasing the number of trucks to meet freight demands;
	(5) Truck configurations that minimize the detrimental effect on bridges. Demonstration of the method will be provided with Alabama Bridge Case Study;
	(6) Investigate the Florida I-Beam (FIB) Girders under Heavy Vehicle Load (Review Development of Bridges, Loads, Characteristics, Advantages of New

	Bridges under given loads)
	(7) Development of FE Models of 3 Bridges (w/AASHTO & FIB Girders) (Detailed Model Details, Evaluation, Load Rating Analysis)
Describe Implementation of Research Outcomes (or why not implemented) (Attach Any Photos)	 A method to characterize the representative vehicle including the gross vehicle weight and axle load over a return period of interest. A method and tool to characterize the bridge population sensitive to the load effect and fatigue The simulation and code can be used for both steel girder and prestressed concrete bridges; and for innovative bridge solutions The simulation and code can be used to investigate the effects of different span lengths The simulation and code can be used to account for the different classes of road surface roughness Investigate effect of dynamic loading including the impact increasing number of heavy vehicles and/or the vehicle weight limit on the service life of bridges. 2D and 3D simulation technique, and written MATLAB code can be used to determine the static and dynamic responses of bridges traveling on the bridge and for different combination of truck loads; and different vehicle speeds on the dynamic response of bridges
	 Significant results from the current quarter includes the following: Task 1: Develop heavy vehicle-bridge interaction model to quantify the effect of meeting increasing freight demands on bridges. Derivations of equations of the motion for different types of trucks (FIU) – 100% Develop Truck Models and Bridge Types (UAB + FIU) – 90% Detailed FE Modeling of a Bridge (UAB) – 100%
	 Task 2. Compare the effect of heavier trucks to the effect of doubling the number of heavy vehicles under the present legal weight restrictions. Design of steel and prestressed concrete bridges with different span lengths (FIU) -100% Write MATLAB code to solve the interaction equations for the vehicle models and beam system (FIU) - 100% Dynamic Analysis of bridge due to moving vehicles (UAB+FIU) – 30% Task 3. Characterize the traffic measured by WIM data in terms of its influence on characteristic bridge load effect Characterize WIM data to detect the most reasonable expected extreme gross vehicle weight (UAB) – 100% Determine the characteristic Bridge under traffic load effects and Fatigue by WIM Data (UAB+UCF) – 80%





	 Knowing the trends in permits weights in excess of legal limits and resulting damage costs with appropriate design solutions and actions is extremely important:
	 Better utilization of bridges
	 Possible increase in load demands within safety limits
	 Understanding damage locations for condition-based maintenance of bridges
	 Making long-term programmatic decision regarding truck size and weight that in the best interest of our transportation infrastructure.
	 Some bridge response measures such as the Dynamic Amplification Factor (DAF) of bridges will be obtained. These measures have important effects on the design of highway bridges and also to understand the durability of current bridges.
Web Links	In Progress; not ready yet
 Reports Project website	